Flight Mill Wiring Components and Software

Image	Item Name	Item#	Description
	NI PCI-6503 and NI-DAQ Software	777690-01	 User-defined power-up state 2-wire handshake capability 24 lines (5 V/TTL) static I/O in 8-bit ports, 2.4 mA NI-DAQmx driver software for easy configuration Unidirectional and bidirectional I/O For applications requiring more than 24 digital I/O channels consider PCI-6509
National Control of the Control of t	CB-50LP Connector Block w/o Cable	777101-01	 Dimensions: 13.26 by 7.19 cm (5.22 by 2.83 in.) Low-cost accessory with 50 screw terminals for easily connecting field I/O signals to your DAQ board Metal standoffs for use on a desktop or for mounting on a custom panel One 50-pin header for directly connecting to 50-pin cables Use with the CA-1000 for configurable connections
The state of the s	Cable Assy, 50P, Flat, NB1, 1M	180524-10	 Connects to 50-pin connector accessories Download PDF for compatibility charts, more detailed descriptions, and ordering information Variety of length options 50-pin ribbon cable for any board with a 50-pin connector
A SECURITY OF THE PROPERTY OF	LABVIEW Full Development System, Windows, 1 yr. Std. Srv.	776670-09	 Easy-to-use graphical development environment Tight integration with a wide range of measurement hardware Rapid user interface development for displaying live data Extensive signal processing, analysis, and math functionality Multiple communication options (TCP/IP, UDP, serial, and more) Support for Windows XP/Vista/7 (32-bit) and Windows Vista/7 (64-bit)

National Instruments Corp., 11500 N. Mopac Expressway, Austin, TX 78759-3504 USA phone: 512-683-0100 website: http://www.ni.com/